

**Antenna VHF**

made with the Fast Fit system (removable screw-type) in chrome-plated brass and seals, ensuring maximum protection of the connector from external agents. Standard 1" x 14 thread connection



Article	Colour	Length cm.	Cable mt.	Connector	Freq. Mhz	Max. Power W	VSWR	Gain dB
<b>5555113</b>	White	150	-	N°1 type "N" (F)	156-162	50	<1,5:1	3

**Antenna VHF**


mast head with stainless steel bracket

**5555111****5555108****5555107**

Article	Colour	Length cm.	Cable mt.	Connector	Freq. Mhz	Max. Power W	VSWR	Gain dB
5555111	White	18	18	Nº1 PL259 (F) e 1 (M)	156-162	50	<1,5:1	1
5555108		90	-	Nº1 PL259 (F)				3
5555107	Inox	100	-					

**VHF antenna for masthead with Windex 15 indicator**

VHF antenna in reinforced fiberglass, UV resistant, high performance combined with Windex wind indicator placed directly on the top of the antenna. It is supplied with a stainless steel mounting bracket.



The Windex 15 is firmly connected to the antenna by a chromed brass joint. Thanks to its famous suspension system with sapphire bearings it allows the indication of wind in all weather conditions, including very light winds up to 2 tenths of a node.



Article	Colour	Length cm.	Connector	Freq. Mhz	Max. Power W	Gain dB
<b>5555126</b>	Bianco	55	N°1 tipo "N" (F)	156-162	50	1
<b>5555127</b>		90				3

**Antenna radio AM/FM**

**5555115** flexible white removable by screw, base Ø mm.60 with waterproof seal inside.



**5555116**  
Standard 1" x 14 thread connection.

Article	Length. cm	Cable mt.	Freq. Mhz
<b>5555115</b>	25	4 + jack connector	88-108
<b>5555116</b>	90		